

Rethync Multisite steel hoarding is a high quality reusable in ground system designed primarily for housebuilders and construction companies. It can readily be moved from site to site thereby providing savings for owners in terms of both cost and the environment.

PRODUCT INFORMATION

Hoarding

Multisite hoarding is 2.4m high as standard. This can be extended to 3m high by adding extension arms to the post tops for the fixing of barbed wire or razor tape security topping.

The system infill is of 1m wide panels that are overlapped within the system framework so that a continuous run of hoarding of any length is possible without having posts or fittings to external view.

The steel panels are galvanised both sides and powder coated white on one side as standard. Other colours can be provided upon request to enable corporate colour matching.

Posts are supplied in galvanised finish and fittings are galvanised or zinc plated.

Multisite hoarding can accommodate gently sloping ground without the need for stepping. It can similarly curve through gentle changes of direction.

Backstays are not required for standard installations thereby enabling maximum usable internal compound space.

Pedestrian Access Gates

These single leaf gates are 1.1m wide and are clad in the same steel sheet as the main fence run. 5 lever locks to BS3621:2007 are included as standard but fitted digi locks are available as an optional extra if so required.

Vision Panels

These are made from clear polycarbonate and can be of any dimension as specified by the customer. They are fitted flush into the hoarding line and are often used as a safety or security feature by improving through visibility and sight lines.

Vehicle Access Gates

Three main designs of double leaf gate are available as standard, all are 5.4m wide, mounted on galvanised gateposts, have drop bolts on each leaf, and include hasp and staple on both sides so that the gates can be locked from inside or out:

- **1.** Standard gates clad in the same steel sheet as the main hoarding fenceline.
- 2. Standard gates clad fully or partly with welded mesh in lieu of steel sheeting.
- 3. 'Barn door' style gates that only open through the top half of the fenceline. The bottom half is solid hoarding. These gates allow various types of mechanical plant to access inside the compound but personnel are kept out.



Security padlocks can be provided as an optional extra with all of these gate styles.





Rethync Ltd was formed in 2017 by a group of people with many years of experience working for others in the fencing and site hoarding industry but who wanted to challenge ourselves to set a new and higher standard of service for customers in this market via our own company.

Our company name was chosen with care as our key company and personal focus is to continually Rethync how our products are supplied and installed and how our services are provided.



RETHYNC

Rethync Ltd. Unit 12, West Moor Park Network Centre Yorkshire Way, Armthorpe, Doncaster, DN3 3GW

3 03300 535 898

For more information please email info@rethync.co.uk or visit: **WWW.rethync.co.uk**







